

linea xs/xc connection cable

TECHNICAL DATASHEET

linea xs/xc connection cable

Technical Data

Dimensions

- Outer diameter cable: 11 mm [0.43 in]
- Outer diameter plug: 35 mm [1.38 in]
- Minimum bending radius fixed: 4 x outer diameter
- Minimum bending radius casually shifted : 15 x outer diameter

Standard Unit Lengths

305 mm, 915 mm, 1525 mm, 3050 mm
12.01 in, 36.03 in, 60.04 in, 120.08 in


Operating Temperature

-40 °C / +80 °C | -40 °F / +176 °F

Ingress Protection

IP66

Environment



Certification



Project	Fixture#	Date
		Firm



Ordering Information

Choose the option that suits your needs and write its corresponding code on the appropriate line to form the product code.

LIN-XSXC-CON- _____ - Y01 _____
FIXTURE LENGTH

FIXTURE LENGTH	
305/1	305 mm / 12.01 in
915/3	915 mm / 36.02 in
1525/5	1525 mm / 60.04 in
3050/10	3050 mm / 120.08 in

* Project-specific options are available - Please contact our Sales Representative for further information.



Lindberghstrasse 15
86343 Koenigsbrunn
Tel: +49 (0)8231/95787-0
Fax: +49 (0)8231/95787-29
www.biontechnologies.com
info@biontechnologies.com

YouTube: <http://www.youtube.com/user/BIONTECHNOLOGIES>

© 2023, BION TECHNOLOGIS GMBH
All rights reserved / Subject to change / Specifications may change without notice