



linea m eco indoor

RGB | RGBW

SPECIFICATION SHEET

BION TECHNOLOGIES GMBH

Lindberghstrasse 15
86343 Koenigsbrunn

Tel: +49 (0)8231/95787-0
Fax: +49 (0)8231/95787-29

www.biontechnologies.com
info@biontechnologies.com

YouTube: <http://www.youtube.com/BIONTECHNOLOGIES>

© 2016, BION TECHNOLOGIS GMBH
All rights reserved / Subject to change / Specifications may change without notice.

Project	Fixture#	Date
		Firm



Ordering Information

Choose the option that suits your needs and write its corresponding code on the appropriate line to form the product code.

LIN-M-ECO-IN- _____ - _____ - _____ - _____ - _____ - _____ - Y03

TYP - LUMINOUS COLOR	DIMMING	BEAM ANGLE	HOUSING COLOR	LEADERCABLE LENGTH	GLARE PROTECTION	MOUNTING OPTION																																																																			
<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th colspan="2">TYP - LUMINOUS COLOR</th> </tr> </thead> <tbody> <tr><td>RGBS</td><td>RGB</td></tr> <tr><td>RGBW22</td><td>RGBW - 2200 K</td></tr> <tr><td>RGBW27</td><td>RGBW - 2700 K</td></tr> <tr><td>RGBW30</td><td>RGBW - 3000 K</td></tr> <tr><td>RGBW40</td><td>RGBW - 4000 K</td></tr> </tbody> </table>		TYP - LUMINOUS COLOR		RGBS	RGB	RGBW22	RGBW - 2200 K	RGBW27	RGBW - 2700 K	RGBW30	RGBW - 3000 K	RGBW40	RGBW - 4000 K	<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th colspan="2">BEAM ANGLE</th> </tr> </thead> <tbody> <tr><td>8X8</td><td>8° x 8°</td></tr> <tr><td>10X10</td><td>10° x 10°</td></tr> <tr><td>23X23</td><td>23° x 23°</td></tr> <tr><td>43X43</td><td>43° x 43°</td></tr> <tr><td>52X52</td><td>52° x 52°</td></tr> <tr><td>8X31</td><td>8° x 31°</td></tr> <tr><td>10X42</td><td>10° x 42°</td></tr> <tr><td>12X60</td><td>12° x 60°</td></tr> <tr><td>14X100</td><td>14° x 100°</td></tr> <tr><td>30X60</td><td>30° x 60°</td></tr> <tr><td>20X60Y10R</td><td>20° x 60° (Tilt in C0-plane: 10°)</td></tr> <tr><td>20X60Y10L</td><td>20° x 60° (Tilt in C0-plane: -10°)</td></tr> </tbody> </table>		BEAM ANGLE		8X8	8° x 8°	10X10	10° x 10°	23X23	23° x 23°	43X43	43° x 43°	52X52	52° x 52°	8X31	8° x 31°	10X42	10° x 42°	12X60	12° x 60°	14X100	14° x 100°	30X60	30° x 60°	20X60Y10R	20° x 60° (Tilt in C0-plane: 10°)	20X60Y10L	20° x 60° (Tilt in C0-plane: -10°)	<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th colspan="2">LEADERCABLE LENGTH</th> </tr> </thead> <tbody> <tr><td>ETE</td><td>End to end - wiring</td></tr> <tr><td>003</td><td>+ 30 cm (ca. 1 ft)</td></tr> <tr><td>006</td><td>+ 60 cm (ca. 2 ft)</td></tr> <tr><td>009</td><td>+ 90 cm (ca. 3 ft)</td></tr> <tr><td>012</td><td>+ 1,2 m (ca. 4 ft)</td></tr> </tbody> </table>		LEADERCABLE LENGTH		ETE	End to end - wiring	003	+ 30 cm (ca. 1 ft)	006	+ 60 cm (ca. 2 ft)	009	+ 90 cm (ca. 3 ft)	012	+ 1,2 m (ca. 4 ft)	<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th colspan="2">GLARE PROTECTION</th> </tr> </thead> <tbody> <tr><td>OP</td><td>No glare protection</td></tr> <tr><td>HL</td><td>Hex louver (internal)</td></tr> <tr><td>LL0</td><td>Linear louver (internal)</td></tr> </tbody> </table>		GLARE PROTECTION		OP	No glare protection	HL	Hex louver (internal)	LL0	Linear louver (internal)	<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th colspan="2">MOUNTING OPTION</th> </tr> </thead> <tbody> <tr><td>MPA</td><td>Mounting Plate Basic</td></tr> <tr><td>MSH</td><td>Mounting Set Hinge</td></tr> </tbody> </table>		MOUNTING OPTION		MPA	Mounting Plate Basic	MSH	Mounting Set Hinge
TYP - LUMINOUS COLOR																																																																									
RGBS	RGB																																																																								
RGBW22	RGBW - 2200 K																																																																								
RGBW27	RGBW - 2700 K																																																																								
RGBW30	RGBW - 3000 K																																																																								
RGBW40	RGBW - 4000 K																																																																								
BEAM ANGLE																																																																									
8X8	8° x 8°																																																																								
10X10	10° x 10°																																																																								
23X23	23° x 23°																																																																								
43X43	43° x 43°																																																																								
52X52	52° x 52°																																																																								
8X31	8° x 31°																																																																								
10X42	10° x 42°																																																																								
12X60	12° x 60°																																																																								
14X100	14° x 100°																																																																								
30X60	30° x 60°																																																																								
20X60Y10R	20° x 60° (Tilt in C0-plane: 10°)																																																																								
20X60Y10L	20° x 60° (Tilt in C0-plane: -10°)																																																																								
LEADERCABLE LENGTH																																																																									
ETE	End to end - wiring																																																																								
003	+ 30 cm (ca. 1 ft)																																																																								
006	+ 60 cm (ca. 2 ft)																																																																								
009	+ 90 cm (ca. 3 ft)																																																																								
012	+ 1,2 m (ca. 4 ft)																																																																								
GLARE PROTECTION																																																																									
OP	No glare protection																																																																								
HL	Hex louver (internal)																																																																								
LL0	Linear louver (internal)																																																																								
MOUNTING OPTION																																																																									
MPA	Mounting Plate Basic																																																																								
MSH	Mounting Set Hinge																																																																								
<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th colspan="2">DIMMING</th> </tr> </thead> <tbody> <tr> <td> </td> <td> </td> </tr> </tbody> </table>		DIMMING				<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th colspan="2">HOUSING COLOR</th> </tr> </thead> <tbody> <tr><td>AA</td><td>Aluminium anodized (Standard)</td></tr> <tr><td>BA</td><td>Black anodized</td></tr> </tbody> </table>		HOUSING COLOR		AA	Aluminium anodized (Standard)	BA	Black anodized																																																												
DIMMING																																																																									
HOUSING COLOR																																																																									
AA	Aluminium anodized (Standard)																																																																								
BA	Black anodized																																																																								

Sample Order Code: linea-m-eco-in-RGBS-dim-DMX-3/922-43x43-AA-Y01

* Project-specific options are available - Please contact our Sales Representative for further information.