



linea m eco

RGBW

SPECIFICATION SHEET

BION TECHNOLOGIES GMBH

Lindberghstrasse 15
86343 Koenigsbrunn

Tel: +49 (0)8231/95787-0
Fax: +49 (0)8231/95787-29

www.biontechnologies.com
info@biontechnologies.com

YouTube: <http://www.youtube.com/BIONTECHNOLOGIES>

© 2016, BION TECHNOLOGIS GMBH
All rights reserved / Subject to change / Specifications may change without notice.

Project	Fixture#	Date
		Firm



Ordering Information

Choose the option that suits your needs and write its corresponding code on the appropriate line to form the product code.

LIN-M-ECO- _____ - _____ - _____ - _____ - _____ - _____ - _____ - _____ - Y03

TYP - LUMINOUS COLOR		DIMMING	FIXTURE LENGTH	BEAM ANGLE	WIRING	HOUSING COLOR	POSITION LEADER CABLE	LEADERCABLE LENGTH	GLARE PROTECTION	MOUNTING OPTION
TYP - LUMINOUS COLOR RGBW22 RGBW - 2200 K RGBW27 RGBW - 2700 K RGBW30 RGBW - 3000 K RGBW40 RGBW - 4000 K		DIMMING DMX Dimmable - DMX 0-10V Dimmable - 0-10V DALI Dimmable - DALI	FIXTURE LENGTH 629 629 mm / 24.76 in 934 934 mm / 36.77 in 1239 1239 mm / 48.78 in	BEAM ANGLE 8X8 8° x 8° 10X10 10° x 10° 23X23 23° x 23° 43X43 43° x 43° 8X31 8° x 31° 10X42 10° x 42° 12X60 12° x 60° 14X100 14° x 100° 30X60 30° x 60° 60X30 60° x 30°	WIRING CE Europe ETL North America	HOUSING COLOR AA Aluminium anodized (Standard) BA Black anodized	POSITION LEADER CABLE L Left R Right	LEADERCABLE LENGTH ETE End to end - wiring 003 + 30 cm (ca. 1 ft) 006 + 60 cm (ca. 2 ft) 009 + 90 cm (ca. 3 ft) 012 + 1,2 m (ca. 4 ft)	GLARE PROTECTION OP No glare protection HL Hex louver (internal) LLO Linear louver (internal)	MOUNTING OPTION MX00 Mounting bracket Fix 0° MX20 Mounting bracket Fix 20° MSH Mounting Set Hinge

Sample Order Code: linea-m-eco-out-RGBW30-dim-DMX-4/1228-52x52-AA-Y01

* Project-specific options are available - Please contact our Sales Representative for further information.