



linea m hp

tunableWhite

SPECIFICATION SHEET

BION TECHNOLOGIES GMBH

Lindberghstrasse 15
86343 Koenigsbrunn

Tel: +49 (0)8231/95787-0
Fax: +49 (0)8231/95787-29

www.biontechnologies.com
info@biontechnologies.com

YouTube: <http://www.youtube.com/BIONTECHNOLOGIES>

© 2016, BION TECHNOLOGIS GMBH
All rights reserved / Subject to change / Specifications may change without notice.

Project	Fixture#	Date
		Firm



Ordering Information

Choose the option that suits your needs and write its corresponding code on the appropriate line to form the product code.

LIN-M-HP- TW2240 - DIMMING - FIXTURE LENGTH - BEAM ANGLE - WIRING - HOUSING COLOR - POSITION LEADER CABLE - LEADERCABLE LENGTH - GLARE PROTECTION - MOUNTING OPTION - Y03

TYP - LUMINOUS COLOR		DIMMING		FIXTURE LENGTH		BEAM ANGLE		WIRING		HOUSING COLOR		POSITION LEADER CABLE		LEADERCABLE LENGTH		GLARE PROTECTION		MOUNTING OPTION									
TYP - LUMINOUS COLOR		DIMMING		FIXTURE LENGTH		BEAM ANGLE		WIRING		HOUSING COLOR		POSITION LEADER CABLE		LEADERCABLE LENGTH		GLARE PROTECTION		MOUNTING OPTION									
TW2240	tunableWhite - 2200 K - 4000 K	DMX	Dimmable - DMX	8X8	8° x 8°	L	Left	ETE	End to end - wiring	AA	Aluminium anodized (Standard)	OP	No glare protection	MX00	Mounting bracket Fix 0°	CE	Europe	HL	Hex louver (internal)	MX20	Mounting bracket Fix 20°	ETL	North America	LL0	Linear louver (internal)	MSH	Mounting Set Hinge
0-10V	Dimmable - 0-10V	10X10	10° x 10°	10X42	10° x 42°	R	Right	003	+ 30 cm (ca. 1 ft)	BA	Black anodized	006	+ 60 cm (ca. 2 ft)	009	+ 90 cm (ca. 3 ft)												
DALI	Dimmable - DALI	23X23	23° x 23°	12X60	12° x 60°			012	+ 1,2 m (ca. 4 ft)																		
		43X43	43° x 43°	14X100	14° x 100°																						
		8X31	8° x 31°	30X60	30° x 60°																						
		10X42	10° x 42°	60X30	60° x 30°																						

Sample Order Code: linea-m-hp-outdoor-tw3060-dim-DMX-2/617-10x10-TA-Y01

* Project-specific options are available - Please contact our Sales Representative for further information.