



linea xs hp

tunableWhite

SPECIFICATION SHEET

BION TECHNOLOGIES GMBH

Lindberghstrasse 15
86343 Koenigsbrunn

Tel: +49 (0)8231/95787-0
Fax: +49 (0)8231/95787-29

www.biontechnologies.com
info@biontechnologies.com

YouTube: <http://www.youtube.com/BIONTECHNOLOGIES>

© 2016, BION TECHNOLOGIS GMBH
All rights reserved / Subject to change / Specifications may change without notice.

Project	Fixture#	Date
		Firm



Ordering Information

Choose the option that suits your needs and write its corresponding code on the appropriate line to form the product code.

LIN-XS-HP- TW2240 - - - - - Y01

TYP - LUMINOUS COLOR	DIMMING	FIXTURE LENGTH	BEAM ANGLE	HOUSING COLOR	GLARE PROTECTION	WIRING CONFIGURATION	LEADERCABLE LENGTH	MOUNTING OPTION
TYP - LUMINOUS COLOR								
TW2240 tunableWhite - 2200 K - 4000 K								
DIMMING								
DALI Dimmable - DALI								
DMX Dimmable - DMX								
FIXTURE LENGTH								
324 324 mm / 12.76 in								
477 477 mm / 18.78 in								
629 629 mm / 24.76 in								
782 782 mm / 30.79 in								
934 934 mm / 36.77 in								
1087 1087 mm / 42.8 in								
1239 1239 mm / 48.78 in								
		BEAM ANGLE						
		8X8 8° x 8°						
		10X10 10° x 10°						
		23X23 23° x 23°						
		43X43 43° x 43°						
		8X31 8° x 31°						
		10X42 10° x 42°						
		12X60 12° x 60°						
		14X100 14° x 100°						
		30X60 30° x 60°						
		60X30 60° x 30°						
				HOUSING COLOR				
				AA Aluminium anodized (Standard)				
				BA Black anodized				
					GLARE PROTECTION			
					OP No glare protection			
					HL Hex louver (internal)			
					LL0 Linear louver (internal)			
						WIRING CONFIGURATION		
						IOCC IN/OUT with Connector		
						IXCX only IN with Connector		
						IOOC IN open end / OUT socket		
						IOOO IN/OUT with open ends		
						IXOX only IN with open ends		
							LEADERCABLE LENGTH	
							ETE End to end - wiring	
							003 + 30 cm (ca. 1 ft)	
							006 + 60 cm (ca. 2 ft)	
							009 + 90 cm (ca. 3 ft)	
							012 + 1,2 m (ca. 4 ft)	
								MOUNTING OPTION
								ND without bracket
								BS Universal mounting bracket

* Project-specific options are available - Please contact our Sales Representative for further information.