



tantulus hp outdoor

pureWhite

SPECIFICATION SHEET

BION TECHNOLOGIES GMBH

Lindberghstrasse 15
86343 Koenigsbrunn

Tel: +49 (0)8231/95787-0
Fax: +49 (0)8231/95787-29

www.biontechnologies.com
info@biontechnologies.com

YouTube: <http://www.youtube.com/BIONTECHNOLOGIES>

© 2016, BION TECHNOLOGIS GMBH
All rights reserved / Subject to change / Specifications may change without notice.

Project	Fixture#	Date
		Firm

Ordering Information

Choose the option that suits your needs and write its corresponding code on the appropriate line to form the product code.

TAN-OUT-HP-- _____ - _____ - _____ - _____ - Y31

TYP - LUMINOUS COLOR
FIXTURE LENGTH
BEAM ANGLE
MOUNTING OPTION

TYP - LUMINOUS COLOR	
PW26	pureWhite - 2600 K
PW33	pureWhite - 3300 K
PW40	pureWhite - 4000 K
PW44	pureWhite - 4400 K

MOUNTING OPTION	
K0	Bracket Set 0°
K15	Bracket Set 15°
K30	Bracket Set 30°
K45	Bracket Set 45°
K60	Bracket Set 60°
KADJ	Positioning Hinge
<small>Fixed Angle: Bracket count: 2 <= 1225 mm (48.23 in) > 3 HKadj: Bracket count: 2 for all lengths</small>	

FIXTURE LENGTH	
310	310 mm / 12.2 in
615	615 mm / 24.21 in
920	920 mm / 36.22 in
1225	1225 mm / 48.23 in
1530	1530 mm / 60.24 in
1835	1835 mm / 72.24 in

BEAM ANGLE	
30X120F	30° x 120° frost
120X120W	120° x 120° white
120X120F	120° x 120° frost
SQR(W)	160° x 160° white

* Project-specific options are available - Please contact our Sales Representative for further information.