



tellus surface xhp

pureWhite

SPECIFICATION SHEET

BION TECHNOLOGIES GMBH

Lindberghstrasse 15
86343 Koenigsbrunn

Tel: +49 (0)8231/95787-0
Fax: +49 (0)8231/95787-29

www.biontechnologies.com
info@biontechnologies.com

YouTube: <http://www.youtube.com/BIONTECHNOLOGIES>

© 2016, BION TECHNOLOGIS GMBH
All rights reserved / Subject to change / Specifications may change without notice.

Project	Fixture#	Date
		Firm



Ordering Information

Choose the option that suits your needs and write its corresponding code on the appropriate line to form the product code.

TEL-S-XHP- _____ - _____ - _____ - _____ - _____ - _____ - Y01

TYP - LUMINOUS COLOR	DIMMING	FIXTURE LENGTH	BEAM ANGLE	WIRING	HOUSING COLOR	GLARE PROTECTION	POSITION LEADER CABLE																																																																																
<table border="1"> <thead> <tr> <th colspan="2">TYP - LUMINOUS COLOR</th> </tr> </thead> <tbody> <tr> <td>PW22</td> <td>pureWhite - 2200 K</td> </tr> <tr> <td>PW27</td> <td>pureWhite - 2700 K</td> </tr> <tr> <td>PW30</td> <td>pureWhite - 3000 K</td> </tr> <tr> <td>PW35</td> <td>pureWhite - 3500 K</td> </tr> <tr> <td>PW40</td> <td>pureWhite - 4000 K</td> </tr> </tbody> </table>	TYP - LUMINOUS COLOR		PW22	pureWhite - 2200 K	PW27	pureWhite - 2700 K	PW30	pureWhite - 3000 K	PW35	pureWhite - 3500 K	PW40	pureWhite - 4000 K	<table border="1"> <thead> <tr> <th colspan="2">DIMMING</th> </tr> </thead> <tbody> <tr> <td>NDIM</td> <td>Non-dimmable</td> </tr> <tr> <td>DMX</td> <td>Dimmable - DMX</td> </tr> <tr> <td>IOT</td> <td>Dimmable - IOT</td> </tr> <tr> <td>0-10V</td> <td>Dimmable - 0-10V</td> </tr> <tr> <td>DALI</td> <td>Dimmable - DALI</td> </tr> </tbody> </table>	DIMMING		NDIM	Non-dimmable	DMX	Dimmable - DMX	IOT	Dimmable - IOT	0-10V	Dimmable - 0-10V	DALI	Dimmable - DALI	<table border="1"> <thead> <tr> <th colspan="2">FIXTURE LENGTH</th> </tr> </thead> <tbody> <tr> <td>352</td> <td>352 mm / 13.86 in</td> </tr> <tr> <td>657</td> <td>657 mm / 25.87 in</td> </tr> </tbody> </table>	FIXTURE LENGTH		352	352 mm / 13.86 in	657	657 mm / 25.87 in	<table border="1"> <thead> <tr> <th colspan="2">BEAM ANGLE</th> </tr> </thead> <tbody> <tr> <td>7X7</td> <td>7° x 7°</td> </tr> <tr> <td>13X13</td> <td>13° x 13°</td> </tr> <tr> <td>30X30</td> <td>30° x 30°</td> </tr> <tr> <td>66X66</td> <td>66° x 66°</td> </tr> <tr> <td>8X31</td> <td>8° x 31°</td> </tr> <tr> <td>11X45</td> <td>11° x 45°</td> </tr> <tr> <td>12X60</td> <td>12° x 60°</td> </tr> </tbody> </table>	BEAM ANGLE		7X7	7° x 7°	13X13	13° x 13°	30X30	30° x 30°	66X66	66° x 66°	8X31	8° x 31°	11X45	11° x 45°	12X60	12° x 60°	<table border="1"> <thead> <tr> <th colspan="2">WIRING</th> </tr> </thead> <tbody> <tr> <td>CE</td> <td>Europe</td> </tr> <tr> <td>ETL</td> <td>North America</td> </tr> </tbody> </table>	WIRING		CE	Europe	ETL	North America	<table border="1"> <thead> <tr> <th colspan="2">HOUSING COLOR</th> </tr> </thead> <tbody> <tr> <td>DB</td> <td>DB703 powdercoated</td> </tr> <tr> <td>WH</td> <td>White powdercoated</td> </tr> <tr> <td>BL</td> <td>Black powdercoated</td> </tr> <tr> <td>RAL____</td> <td>Custom Color RAL</td> </tr> </tbody> </table>	HOUSING COLOR		DB	DB703 powdercoated	WH	White powdercoated	BL	Black powdercoated	RAL____	Custom Color RAL	<table border="1"> <thead> <tr> <th colspan="2">GLARE PROTECTION</th> </tr> </thead> <tbody> <tr> <td>OP</td> <td>No glare protection</td> </tr> <tr> <td>HL</td> <td>Honeycomb louver</td> </tr> <tr> <td>LL00</td> <td>Linear louver 0°</td> </tr> <tr> <td>CGC</td> <td>customized glare control</td> </tr> <tr> <td colspan="2">Use LL17 only with beam angle www or wwn</td> </tr> </tbody> </table>	GLARE PROTECTION		OP	No glare protection	HL	Honeycomb louver	LL00	Linear louver 0°	CGC	customized glare control	Use LL17 only with beam angle www or wwn		<table border="1"> <thead> <tr> <th colspan="2">POSITION LEADER CABLE</th> </tr> </thead> <tbody> <tr> <td>ZS</td> <td>side feed</td> </tr> <tr> <td>ZR</td> <td>back feed</td> </tr> </tbody> </table>	POSITION LEADER CABLE		ZS	side feed	ZR	back feed
TYP - LUMINOUS COLOR																																																																																							
PW22	pureWhite - 2200 K																																																																																						
PW27	pureWhite - 2700 K																																																																																						
PW30	pureWhite - 3000 K																																																																																						
PW35	pureWhite - 3500 K																																																																																						
PW40	pureWhite - 4000 K																																																																																						
DIMMING																																																																																							
NDIM	Non-dimmable																																																																																						
DMX	Dimmable - DMX																																																																																						
IOT	Dimmable - IOT																																																																																						
0-10V	Dimmable - 0-10V																																																																																						
DALI	Dimmable - DALI																																																																																						
FIXTURE LENGTH																																																																																							
352	352 mm / 13.86 in																																																																																						
657	657 mm / 25.87 in																																																																																						
BEAM ANGLE																																																																																							
7X7	7° x 7°																																																																																						
13X13	13° x 13°																																																																																						
30X30	30° x 30°																																																																																						
66X66	66° x 66°																																																																																						
8X31	8° x 31°																																																																																						
11X45	11° x 45°																																																																																						
12X60	12° x 60°																																																																																						
WIRING																																																																																							
CE	Europe																																																																																						
ETL	North America																																																																																						
HOUSING COLOR																																																																																							
DB	DB703 powdercoated																																																																																						
WH	White powdercoated																																																																																						
BL	Black powdercoated																																																																																						
RAL____	Custom Color RAL																																																																																						
GLARE PROTECTION																																																																																							
OP	No glare protection																																																																																						
HL	Honeycomb louver																																																																																						
LL00	Linear louver 0°																																																																																						
CGC	customized glare control																																																																																						
Use LL17 only with beam angle www or wwn																																																																																							
POSITION LEADER CABLE																																																																																							
ZS	side feed																																																																																						
ZR	back feed																																																																																						

* Project-specific options are available - Please contact our Sales Representative for further information.